


JCH ball valve Type 745513

With female threads. Full bore.

VA and SITAC approved.

Prepared for AVK extension spindles and street covers.



Version 0116



JCH ball valve with female threads:

Applications:

Service valve for water supply and sewage,
Suitable for drilling under pressure.

Test:

JCH 100% test

Accessories:

AVK extension spindles fixed length series 04/05.

AVK extension spindles telescopic series 04/07.


AVK street covers.

Material

Body:	DZR Brass CW625N
Spindle:	Stainless steel - AISI 303
Spindle-gasket:	SEDI PTFE + O-rings of NBR rubber
Ball:	stainless acid proof steel - AISI 316
Top gasket:	NBR O-rings
Top union:	DZR Brass CW602N
Gasket inside:	SEDI PTFE



JCH bal valve Type 745513 with 12mm # operation key. Prepared for AVK extension spindles and street covers.



Version 0116

Ball valve type 745513 is suitable as service valve in water supply and sewage .
The valve can be used for drilling under pressure because of the full bore version.
The valve is quick and easy to install and use.
The valve is made of the finest and best materials.



Order no..	LNS no.	RP	DN mm	L mm	H mm	NV1 mm Spindle	NV2 mm Valve	weight kg
745513-108	343-025-24-00	1"	25	82	104	12	42	1,34
745513-110	343-032-24-00	1¼"	32	103	109	12	56	2,04
745513-111	343-040-24-00	1½"	40	107	119	12	70	2,85
745513-112	343-050-24-00	2"	50	120	127	12	70	3,65

JCH A/S

Karetmagervej 21 DK-7100 Vejle Tel. +45 75 85 84 08 Fax +45 75 85 80 82
CVR-nr. 87 56 20 18 | CVR-nr. DK 15 30 02 72