


JCH ball valve Type 745517 with drain
Prevents frost damage.
With female threads. Reduced bore.
Prepared for AVK extension spindles and street covers.



Version 0116



Reduced bore ball valve with femal threads:

Applications:

Service valve for water supply and sewage.
 Prevents frost damage.

Test:

JCH 100% test

Accessories:

AVK extension spindles fixed lenght series 04/05.

AVK extension spindles telescopic series 04/07.

AVK street covers.


Material

Body:	DZR Brass CW625N
Pipecoupling:	DZR Brass CW625N
Spindle:	Stainless steel - AISI 303
Spindle-gasket:	SEDI PTFE + O-rings of NBR rubber
Ball:	stainless acid proof steel - AISI 316
Top gasket:	NBR O-rings
Top union:	DZR Brass CW602N
Gasket inside:	SEDI PTFE

JCH ball valve Type 745517

with 12mm # operation key.

Prepared for AVK extension spindles and street covers.



Version 0116

Service valve for water supply and sewage.



Order no.	LNS no.	RP "	DN mm	L mm	H mm	NV1 mm spindle	NV2 mm Valve	weight kg
745517-310	343-025-54-10	1¼"	25	97	104	12	42	1,45
745517-311	343-032-54-10	1½"	32	107	109	12	56	1,75
745517-312	343-040-54-10	2"	40	117	119	12	70	2,65

JCH A/S

Karetmagervej 21 DK-7100 Vejle Tel. +45 75 85 84 08 Fax +45 75 85 80 82
CVR-nr. 87 56 20 18 | CVR-nr. DK 15 30 02 72