

Version 0116

Ball valve Type 745511D with drain.

Prevents frost damage.
With male and female threads. Full bore.
Prepared for AVK extension spindle and street cover.



Ball valve with male and female threads:

Application:

Service valve for water supply.

Suitable for drilling under pressure.

Suitable for drainage of water in house installations (summer cottage), to prevent frost damage.

Test:

JCH 100% test

Accessories:

AVK extension spindles fixed length series 04/05.

AVK extension spindles telescopic series 04/07.

AVK street covers.


Material

Body:	DZR Brass CW625N
Spindle:	Stainless steel - AISI 303
Spindle-gasket:	SEDI PTFE + O-rings of NBR rubber
Ball:	Stainless acid proof steel - AISI 316
Top gasket:	NBR O-rings
Top union:	DZR Brass CW602N
Gasket inside:	SEDI PTFE

JCH ball valve Type 745511D

With 12mm # operating key.

Prepared for AVK extension spindles and street covers.



Version 0116

Ball valve type 745511D is made for house installations to prevent frost damage.
When closed the drain port opens and drains the pipe.
The male and female threads gives many different opportunities of connections.
The valve can be used for drilling under pressure because of the full bore version.
The valve is quick and easy to install and use.
The valve is made of the finest and best materials.



Order no.	LNS no.	DN	L1 mm mounted	L2 mm full lenght	H mm	NV1 mm spindle	NV2 mm valve	weight kg
745511-308	343-025-04-10	25	89	107	104	12	42	1,44
745511-310	343-032-04-10	32	100	118	109	12	56	2,14
745511-311	343-040-04-10	40	102	122	119	12	70	2,94

JCH A/S

Karetmagervej 21 DK-7100 Vejle Tel. +45 75 85 84 08 Fax +45 75 85 80 82
CVR-nr. 87 56 20 18 | CVR-nr. DK 15 30 02 72