


Clamped T-connectors / speedfix Type 6441 - 43



Version 0116



Clamped T-connectors Type 6441 - 43

Application:
for mounting on new and older installations of low-flush lavatories wash basins kitchen sinks, washing machines, automatic dishwashers, and for mounting and extension of compressed air plants and sprinkler systems
avoid cuttings, threadings, long screws and tee-pieces.
Applicable for iron and copper tubes
Note: 013762-111 1 1/2"/48mm only for Iron tubes

Test:
JCH's 100% test


Additional parts:
synthetic washers, drills and drilling sockets

Material

Top:	DZR brass CW625N
Lower part:	DZR brass CW625N
washers:	Nitril maks. temp. 90° short
Screws:	Electroplated with Unbacho head
Drill:	HS twist drill
Drilling sockets:	DZR brass CW625N

Clamped T- connectors / speedfix Type 6441 – 43

Speed fix made of DZR brass, to make an extra outlet fast and easy



Version 0116



Components:

- 1.Top
- 2.Lower part
- 3.Screws
- 4.Drilling sockets
- 5.Washer
- 6.HS Twist drill

Order no..	Dimension	Copper tubes	Iron tubes	Pce. Each box.	item	weight Kg
013762-004	½"/22mmCU	✓	✓	10	speedfix	0,170
013762-006	¾"/28mmCU	✓	✓	5	speedfix	0,258
013762-008	1"/35mm CU	✓	✓	5	speedfix	0,285
013762-111	1 ½"/48mm	x	✓	5	Speedfix	0,420
013756-004	8 x 115mm				HS twist drill	0,044
013767-004	½" RG			10	Drilling sockets	0,098
013768-004					Washers	

JCH A/S

Karetmagervej 21 DK-7100 Vejle Tel. +45 75 85 84 08 Fax +45 75 85 80 82
CVR-nr. 87 56 20 18 | CVR-nr. DK 15 30 02 72